




NVR-301S-04L-P4

Network Video Recorder with PoE network interfaces

- 4-channel input
- Plug & Play with 4 independent PoE network interfaces
- Third-party IP cameras supported with ONVIF conformance
- Support 1-ch HDMI, 1-ch VGA
- Up to 2 Megapixels resolution recording
- Support H.265/H.264 video formats with Smart Encoding
- Accurate retrieval, instant playback
- 1 SATA HDD up to 8 TB
- Support for P2P, UPnP, NTP, DHCP, PPPoE
- Support for mobile client access



Specifications

| | |
|-------------------------------|--|
| IP Video Input | 4-ch |
| Incoming bandwidth | 40Mbps |
| Outgoing bandwidth | 40Mbps |
| Remote connection | 128 |
| VGA/ HDMI Output | 1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz |
| Recording Resolution | 1080p/960p/720p/D1/2CIF/CIF |
| Synchronous Playback | 4-ch |
| Compression | H.265/H.264, Smart Encoding |
| Live view/ Playback | 1080p/960p/720p/D1/2CIF/CIF |
| Frame Rate | 2 x 1080p@25fps, 4 x 720p@25fps, 4 x D1@25fps |
| Storage Interface | 1 SATA interface - internal |
| Capacity | up to 8TB for each disk |
| Behavior Detection | Motion detection |
| Network Interface | 1 RJ-45 10M/100M self-adaptive Ethernet Interface |
| Camera PoE Interface | 4 independent 100 Mbps PoE network interfaces |
| Supported PoE Standard | IEEE 802.3at, IEEE 802.3af |
| Network Protocols | HTTP, TCP/IP, IPv4, IPv6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, IP Server, P2P, Telnet (default OFF) |
| USB Interface | Rear panel: 2 x USB2.0 |
| Power Supply | 48V DC |
| Consumption (without HDD) | ≤ 5 W |
| PoE Power Output | Max 30W for single port, Max 54W in total (13.5W for each) |
| Working Temperature | -10°C ~ + 55°C |
| Dimensions / Weight (W/O HDD) | 42 × 205 × 205mm / ≤ 1.12 Kg |