

XVR-7104 H

Features :

- Support 4ch 4K-N unreal-time encoding;
- Support XVI,AHD, TVI,CVI, CVBS, IP video input;
- support VGA maximum 1080P output, HDMI up to 4K output;
- Mini 1U Case, 1SATA(Up to 8TB);
- 1*10/100Mbps auto-sensing Ethernet port, RJ45 port ;
- Automatic networking support, a key to add equipment;
- Support the Onvif protocol;
- Support GB28181 (Optional);
- Cloud services, P2P, alarm information push to phone;
- Support remote access, support ARSP;
- Support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, 3G, WIFI, IP search, Alarm center, etc ;
- Mobile phone remote monitoring (iOS, Android);
- Multi browser access (IE, Chrome, Firefox, Safari);
- Support for more than twenty languages;
- Perfect protection circuit,unique triple watchdog function
- Support WEB, CMS, VMS, MYEYE Platform;
- Support coaxial control

Model :

XVR-7104H

Interface :



Parameters :



	Model	XVR-7104H
System	processor	Hi3520D V400
Video	Codec	H.265+/H.265/H.264
	Encode	4*4K-N@7fps(6 in 1)4*5M@6fps (6 in 1) ; 4*4M@8fps (6 in 1) ;4*3M@10fps (6 in 1) ; 4*1080P@18fps (6 in 1)
	Decode	1*4K-N@7fps(6 in 1)1*5M@6fps (6 in 1) ; 4*4M@8fps (6 in 1) ;4*3M@10fps (6 in 1) ; 4*1080P@18fps (6 in 1)
	preview	4*4K-N@15fps(6 in 1) ; 4*5M@12fps(6 in 1) ;4*4M@15fps(6 in 1) ; 4*3M@18fps (6 in 1) ; 4*1080P(6 in 1)
	Multi-mode	Analog:4*4K-N;4*5M; 4*4M;
		Digital to analog : support(except4*5M, 4+4 hybrid mode)
		Hybird:4*4M(analog)+4*4M (network)
	Playback	IP:16*1080P;8*5M
Audio	Compression	G.711a
	Intercom	Support
Management	Record mode	Manual>Alarm>Motion detection>Timing
	Inquire mode	Inquire by Time/Calendar/Event/Channel
	Storage mode	HDD Storage, Network Storage
	Backup	Network, USB, SATA
Interface	Video input	4*BNC (Support Coaxitron)
	HDMI output	1*HDMI (MAX:4K)
	VGA output	1*VGA (MAX:1080P)
	Audio I/O	1/1
	Alarm I/O	0/0
	Ethernet port	1*10/100Mbps Ethernet port, RJ45 port
	PTZ control	Support for multiple PTZ protocol
	USB Port	2*USB2.0 ports
	HDD	1*SATA interface (Up to 8TB)
General	Temperature	0 °C - + 55 °C
	Humidity	10% -90% RH
	Power supply	12V/2A
	Consumption	<10W (Without HDD)
	Weight	Around1KG
	Dimension	255mm(L)* 236mm(W)* 44mm(H)