

## XVR-7116H

### Features :

- Support 16ch 4K-N unreal-time encoding;
- Support XVI,AHD, TVI,CVI, CVBS, IP video input;
- Support VGA maximum 1080P output, HDMI up to 4K output
- Mini 1U Case, 1 SATA(Up to 8TB);
- 1\*10/100Mbps auto-sensing Ethernet port, RJ45 port ;
- Automatic networking support, a key to add equipment;
- Support the Onvif protocol;
- Support GB28181 (Optional);
- Cloud services, P2P, alarm information push to phone;
- Support remote access, support ARSP;
- Support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, 3G, WIFI, IP search, Alarm center, etc ;
- Mobile phone remote monitoring (iOS, Android);
- Multi browser access (IE, Chrome, Firefox, Safari);
- Support for more than twenty languages;
- Perfect protection circuit,unique triple watchdog function
- Support WEB, CMS, VMS, MYEYE Platform;
- Support coaxial control

### Model :

XVR-7116H

### Interface :



### Parameters :



	Model	XVR-7116H
System	processor	Hi3531D
Video	Codec	H.265+/H.265/H.264
	Encode	16*4K-N@7fps(6 in 1);16*5M@6fps(6 in 1); 16*4M@8fps ( 6 in 1 ) ;16*3M@10fps ( 6 in 1 ) ;16*1080P@12fps(6 in 1)
	Decode	4*4K-N@7fps(6 in 1);4*5M@6fps(6 in 1); 16*4M@8fps ( 6 in 1 ) ;16*3M@10fps ( 6 in 1 ) ;16*1080P@12fps(6 in 1)
	preview	16*4K-N@15fps(6 in 1);16*5M@12fps(6 in 1);16*4M@15fps( 6 in 1 );16*3M@18fps( 6 in 1 ) ;16*1080P(6 in 1)
	Multi-mode	Analog:16*5M;16*4M;16*1080P
		Digital to analog: support ( except 16+16 hybrid mode ) Hybird:16*4M(analog)+16*4M (network) 8*4M(analog)+8*4M (network)
		IP: 8*3M ;4*5M
	Playback	16ch
Audio	Compression	G.711a
	Intercom	Support
Management	Record mode	Manual>Alarm>Motion detection>Timing
	Inquire mode	Inquire by Time/Calendar/Event/Channel
	Storage mode	HDD Storage, Network Storage
	Backup	Network, USB, SATA
Interface	Video input	16*BNC ( Support Coaxitron )
	HDMI output	1*HDMI (MAX:4K)
	VGA output	1*VGA (MAX:1080P)
	Audio I/O	2/1
	Alarm I/O	0/0
	Ethernet port	1*10/100Mbps Ethernet port, RJ45 port
	PTZ control	1*RS485, Support for multiple PTZ protocol
	USB Port	2*USB2.0 ports
	HDD	1*SATA interface (Up to 8TB)
General	Temperature	0 °C - + 55 °C
	Humidity	10% -90% RH
	Power supply	12V/2A
	Consumption	<10W ( Without HDD )
	Weight	Around1KG
	Dimension	255mm(L)* 236mm(W)* 44mm(H)