



## XVR-8108

### 6in1 H.264+ 5MPix AHD, TVI, CVI, XVI, CVBS + IP Video Recorder

- Support 8ch 5M/4M unreal-time encoding
- Support 8ch 1080p realtime video recording
- Support AHD, TVI, CVI, XVI, CVBS, IP video input
- HDMI/VGA simultaneous video output
- Mini 1U Case, 1 SATA(Up to 8TB)
- 1 x 10/100Mbps auto-sensing Ethernet port, RJ45 port
- Automatic networking support, a key to add equipment
- Support Onvif protocol
- Cloud services, P2P, alarm information push to phone
- Support remote access, support ARSP
- Support DHCP, FTP, DNS, DDNS, NTP, UPNP, E-MAIL, 3G, WIFI, IP search, Alarm center, etc
- Mobile phone remote monitoring (iOS, Android)
- Support for more than twenty languages
- Perfect protection circuit, unique triple watchdog function
- Support WEB, CMS, VMS, XMEYE Platform



### Specifications

|                               |   |
|-------------------------------|---|
| Video Input                   | 8 x BNC (Support Coaxitron / XVI Control)                                   |
| Audio Input                   | 4-ch, RCA   |
| HDMI Output                   | 3840x2160, 1920x1080, 1600x1200, 1280x1024, 1280x720, 1024x768              |
| VGA Output                    | 1920x1080, 1600x1200, 1280x1024, 1280x720, 1024x768                         |
| Audio Output                  | 1-ch, RCA   |
| Recording Resolution          | 8 x 5M@11fps(AHD) 8 x 4M@15fps(AHD) 8 x 3M@18fps(AHD) 8 x 1080P@25fps(5in1) |
| Multi mode                    | Hybird: 4 x 5M-max (analog) + 4 x 5M-max (network, NETIP/ONVIF)             |
| NVR / IP-only mode            | 4 x 5M; 8 x 3M  |
| Synchronous Playback          | 4 ch  |
| Compression                   | H.264, H.264+   |
| Storage Interface             | 1 SATA interface - internal   |
| Capacity                      | up to 8TB   |
| Record Mode                   | Manual, Alarm, Motion detection, Timing                                     |
| Inquire mode                  | Inquire by Time/Calendar/Event/Channel                                      |
| Storage mode                  | HDD Storage, Network Storage  |
| Backup                        | Network, USB  |
| Network Interface             | 1 x 10/100Mbps Ethernet port, RJ45 port                                     |
| PTZ Control                   | 1 x RS485, Support for multiple PTZ protocol                                |
| USB Interface                 | 2 x USB2.0 ports  |
| CPU                           | Hi3531A   |
| Alarm I/O                     | 0 / 0   |
| Power Supply                  | 12V/2A  |
| Consumption (without HDD)     | ≤ 15 W  |
| Working Temperature           | 0°C ~ + 55°C  |
| Working Humidity              | 10% -90% RH   |
| Dimensions / Weight (W/O HDD) | 255mm(L) x 236mm(W) x 44mm(H) / 1kg   |