



IPC-600A

7" IP Camera Tester

- 7" 1280x800 IPS touch LCD
- Analog CVBS input + loop test
- H.264 and H.265 video display up to 4K resolution
- Built-in WiFi - Hotspot and Client mode
- LAN/WiFi traffic monitor
- Display ONVIF IP camera image + PTZ
- Included IP Camera Mobile App
- RTSP camera connection supported
- Local FTP server
- Multiple network testing/scanning tools
- 12VDC-in, 7.4V/5000mAh LiPo battery
- Power Output: PoE 24W, 12V/2A, 5V/2A



Specifications

Display	7" touch screen, 1280x800px resolution, IPS technology
Coaxial Signal Support	CVBS, PAL/NTSC auto-sensing
IP Camera Support	ONVIF, ONVIF+PTZ, Videosec, Uniview, xmeye, Hikvision, Dahua, Samsung, Honeywell, ... RTSP Direct Stream Address
Codec Support	H.264, H.265, .mkv, .mp4 local playback
Supported Resolution	up to 4K
Image Zoom	4x image zoom display
Local Recording	Snapshot or Video Recording, both Analog and IP Sources
HDMI Output Support	1ch 1080p
WiFi Operation Mode	b/g/n up to 150Mbps, Client mode or Hotspot mode
LAN port	RJ45, 10/100M auto sensing, PoE Output max 24W
PoE Port Tester	PoE Voltage Test, PoE Link Monitor, PoE Port Flicker
Signal Analysis	Video Level Meter for Analog Cameras, LAN Cable Tester
Cable Tracer	LAN port blinking
Network Tools	PING, IP Scan, Web Browser, FTP Server, ONVIF Tool, ...
Drop-down Menu	PoE out ON/OFF, IP set, WiFi ON/OFF, ...
Serial Port	RS485, 150 to 19200bps, support PTZ Address Scanning, PTZ Data Capture for protocol analysis
Audio In/Out	1Ch Mic/Line, 1Ch Speaker Out, Built-in speaker
Local Storage	removable microSD up to 32GB, 8GB included
LED Lamp	Front edge mounted white LED light source
Power Output	12VDC/2A max, 5VDC/2A max (USB Type A)
Power Input	12VDC charger, 7.4V/5000mAh LiPolymer battery, up to 10h screen-on time, up to 6h charging time
Dimensions - Tester	240x158x44mm, 1kg
Dimensions - Package w. Accessory	320x290x98mm, 2.56kg