




IPW-2122L-40D

2MP Mini Fixed Bullet IR Network PoE Camera



- Day/night functionality
- Smart IR , up to 30m IR distance
- Optical glass window with higher light transmittance
- IR anti-reflection window to increase the infrared transmittance
- 2D/3D-DNR (Digital Noise Reduction)
- H.265, H.264, MJPEG triple streams + Smart Encoding
- ONVIF Conformance
- Wide temperature range: -30°C to 60°C
- Wide voltage range of ±25%
- IP67
- **Full Metal house**, Reset Button
- Junction Box: JB05-IN (optional)



Specifications

Sensor	1/2.7", 2.0 megapixel, progressive scan, CMOS
Shutter	Auto/Manual, 1~1/100000 s
Lens	4.0mm@F2.0 Angle of view(H): 86,5°
Min. Illumination	Colour: 0.02 Lux (F2.0, AGC ON), 0 Lux with IR
Day/Night	IR-cut filter with auto switch (ICR)
IR Range	Up to 30m IR range
S/N	>52 dB
WDR	Digital WDR
Noise Reduction	2D/3D-DNR
Max. Resolution	1920 x 1080
Video Compression	H.265 + Smart Encode, H.264, MJPEG
Frame Rate	1080P (1920*1080): Max. 30 fps; 720P (1280*720): Max. 30 fps; D1 (720*576): Max. 25 fps
ROI	Up to 8 areas
Video Streaming	Triple
OSD	Up to 8 OSDs
Privacy Mask	Up to 8 areas
Motion Detection	22x18 grid / 4 area
General functions	Watermark, IP Address Filtering, Tampering Alarm, Access Policy, ARP Protection, RTSP Authentication, User Authentication
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SSL, TLS, (Telnet default: OFF)
Compatible Integration	ONVIF, API
Network	1 RJ45 10M/100M Base-TX Ethernet
Power	12 V DC ±25%, or PoE (IEEE802.3 af), Power consumption: Max. 4.5 W
Dimensions (Ø x H), Weight	167.3 x 62.9 x 62,7 mm, 0.37 kg
Working Environment	-30°C ~ +60°C, Humidity ≤ 95% RH(non-condensing)
Ingress Protection	IP67