


Network Video Recorder

NVR-301-04LH



Key Features

- Support Ultra265/H.265/H.264 video formats
- 4-channel input
- Third-party IP cameras supported with ONVIF conformance: Profile S, Profile G, Profile T
- Support 1-ch HDMI, 1-ch VGA, HDMI at up to 4K(3840x2160) resolution
- HDMI and VGA simultaneous output
- Up to 4K resolution recording
- 1 SATA HDDs, up to 10 TB
- Support cloud upgrade


Specifications

Model	NVR-301-04LH
Video/Audio Input	
IP Video Input	4-ch (up to 6 after channel expansion)
Network	
Incoming Bandwidth	64Mbps
Outgoing Bandwidth	48Mbps
Remote Users	128
Protocols	P2P, UPnP, NTP, DHCP, PPPoE
Video/Audio Output	
HDMI/VGA Output	HDMI: 3840x2160/30Hz, 1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz VGA: 1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz
Recording Resolution	4K/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
Audio Output	1-ch, 3.5mm Jack
Synchronous Playback	4-ch
Corridor Mode Screen	3/4
Snapshot	
FTP/Schedule/Event Snapshot	1-ch snapshot (max. D1 (720 x 576) video resolution, with D1 snapshot resolution)
Decoding	
Decoding format	Ultra265/H.265/H.264
Live view/Playback	4K/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
Capability	1x4K@30fps, 4x5MP@30fps, 4 x4MP@30 fps, 4x3MP@25 fps, 4x1080p@30 fps
Decoding Capability Description	The resolution of each channel cannot exceed 4000 pixels in length and 3000 pixels in width
Hard Disk	
SATA	1 SATA interfaces
Capacity	Up to 10TB
Smart	
VCA Detection by IPC	Face Detection, Intrusion Detection, Cross Line Detection, Enter Area, Leave Area, IQ Motion Detection (IQM)
Smart by IPC	Total 4-ch (Face Detection, Intrusion Detection, Cross Line Detection, Enter Area, Leave Area, IQM)
VCA Search	Face Snapshot Search, Behavior Search
Capacity of Snapshot Records	2 millions records for face snapshot
Alarm	
General Alarm	Auto Tracking, Motion Detection, Tampering, Human Body Detection, Video Loss, Alarm Input, Audio Detection
Alert Alarm	IP Conflict, Network Disconnected, Disk Offline, Disk Abnormal, Illegal Access, Hard Disk Space Low, Hard Disk Full, Recording/Snapshot Abnormal
External Interface	
Network Interface	1 RJ-45 10M/100M self-adaptive Ethernet Interface
USB Interface	Rear panel: 2 x USB2.0

General

Power Supply	12V DC Power Consumption: ≤5 W (without HDD)
Working Environment	-10°C~+ 55°C, Humidity ≤ 90% RH (non-condensing)
Dimensions (W×D×H)	260mm ×240mm × 46 mm
Weight (without HDD)	≤0,98kg

Dimensions



Rear Panel

