

ODI-201W-R Outdoor Station



Overview

ODI-201W-R is one of the terminal equipment of the digital building intercom system, with video intercom, security alarm, video surveillance, to provide a safe and comfortable living environment for residents. It can be used in villa residential building system.

Key Features

- Built-in 2MP (1920x1080) resolution camera
- Built-In IR LEDs
- Front panel: Aluminium alloy
- Supports batch configuration
- Supports intercom calls to associated indoor units or APPs
- Support monitoring function, security alarm, tamper alarm
- Support wired network and Wi-Fi connection
- Built-in IC card reader (Mifare, 13,56 MHz, 2000pcs)
- Support 12VDC and PoE power supply
- Recessed installation

Specifications

	ODI-201W-R
Resolution	2MP (1920x1080)
WDR	Support
FOV	Horizontal:124.3° Vertical:67.5° Diagonal:147.2°
Sensitivity	0,01lux
Supplement light	IR light (Adaptive infrared compensation), max 10m distance
Operation system	Linux
Volume adjustment	Adjustable
Audio quality	Noise suppression, echo cancellation and AGC
Audio input	1 built-in omnidirectional microphone
Audio output	1 built-in speaker
Audio compression standard	PCM, G711,MP3
Audio compression bitrate	128 kbps
Protocol	Private protocol
Button	1 physical button
Interface	Power *1, Network port *1, WIFI, RS485, door lock interface *2, IO input *4
Network	100Mbps network port, supports IEEE802.3af PoE power supply
Card capacity	2000 Mifare IC card (13,56 Mhz)
Protection level	IP65 (Apply waterproof glue to the gap between the device and the wall. For more information, see the quick guide.) IK08
Power	DC12V±25%, IEEE802.3af, Standard PoE, max. 10W
Dimensions (L×H×W)	79mm× 171mm× 34mm
Operating environment	-30°C -- +60°C, 10% -90%, non-condensing, outdoor
Weight	0.267kg

Dimensions

