

3+1 port PoE Switch

PS03FE+1PD-DIN



Features

- 3*10/100Mbps POE port; 1*10/100Mbps Uplink port;
- ≤100m Distance
- Support IEEE802.3af/at
- Whole Power: 30W
- Support installation on DIN rail or surface

Specification

Model	PS03FE+1PD-DIN
Product	3+1 Port POE Switch
POE Port	1 to 3 support IEEE802.3af/at Standard
Output Power	Max 25W/Average 8,33W
Power Pin	Both 1/2+,3/6- and 4/5+7/8-
Whole Power	≤30W
POE Protocol	IEEE 802.3af/IEEE 802.3at
POE Type	End-span
Power Distance	≤100m
Network Standard	IEEE 802.3, IEEE802.3u,802.3x, 802.3af/at
Network Medium	10/100BASE-TX:5 class and above non shielded twisted pair
Data Distance	≤100m
Switch Capability	1Gbps
Forwarding Mode	Store and forward
Forwarding Rate	10BASE-T:14880PPS/port
	100BASE-tx: 14880pps/port
MAC Address	MAC address table 1K
Port Function	Power priority mechanism, fast and forward, MAC automatic learning and aging
	IEEE802.3X Full-duplex and mode and backpressure for Half-duplex mode
LED Indicator	POE Status Indicator, Whole power indicator
Working Environment	Working temperature: -10°C -- 55°C
Weight	100g
Size	84mm*54mm*27mm(L*W*H), plastic house