

## Desktop switch

PS04FE+2FE-V3



## Key Features

- 10/100Mbps PoE port, 2\*10/100Mbps Up Link port
- 250m Distance
- Support IEEE802.3af/at
- Whole Power: 78W (52V 1.5A)
- All port supported by MDI/MDIX auto flip and self-negotiation
- Supply 4 10/100Mbps adaptive high speed forwarding data packet non-lost port
- Support IEEE802.3x flow control for Full-duplex mode and backpressure for Half-duplex mode
- Each port max. power supply reached 30W

## Specifications

Model	PS04FE+2FE-V3
Product	4 Port PoE Switch (Built-in)
PoE Port	1 to 4 support IEEE802.3at/af Standard
Output Power	15.4W/30W IEEE802.3af/at
Power Pin	Both 1/2+, 3/6- and 4/5+7/8-
Whole Power	≤78W (52V 1.5A)
PoE Protocol	IEEE 802.3af/IEEE 802.3at
PoE Type	End-span
Power Distance	≤250m
Network Standard	IEEE 802.3, IEEE802.3u, 802.3x, 802.3af/at
Network Medium	10/100/1000BASE-TX:5 class and above non shielded twisted pair
Data Distance	≤250m
Switch Capability	1.6Gbps
Forwarding Mode	Store and forward
Forwarding Rate	10BASE-tx:14880pps/port
	100BASE-tx: 148800pps/port
MAC Address	MAC address table 1K
Port Function	Power priority mechanism, fast and forward, MAC automatic learning and aging
	IEEE802.3X Full-duplex and mode and backpressure for Half-duplex mode
LED Indicator	LINK/ACT.100Mbps; POE Status Indicator; Power indicator; Extender indicator
Working Environment	Working temperature: -10°-- 55°C
Weight	850g
Power	230VAC/85W (internal power supply)
Size	200mm*118mm*44mm(L*W*H)