

## Desktop switch

PS04GE+1GE+1SFP



## Key Features

- 4\*100/1000Mbps PoE port, 1\*100/1000Mbps Up Link, 1\*100/1000Mbps SFP
- 100m Distance
- VLAN function
- Support IEEE802.3af/at
- Whole Power:78W (52V 1.5A)
- All port supported by MDI/MDIX auto flip and self-negotiation
- Supply 10\*10/100/1000Mbps adaptive high speed forwarding data packet non-lost port.
- Support IEEE802.3x flow control for Full-duplex mode and backpressure for Half-duplex mode.
- Each port max. power supply reached 30W

### Specifications

Model	PS04GE+1GE+1SFP
Product	4+1+1 Port full Gigabit PoE Switch (Built-in)
PoE Port	1 to 4 support IEEE802.3af/at Standard
Output Power	15.4W/30W IEEE802.3af/at
Power Pin	Both 1/2+, 3/6- and 4/5+7/8-
Whole Power	≤78W (52V 1.5A)
PoE Type	End-span
Power Distance	≤100m
Network Standard	IEEE 802.1s, IEEE 802.1Q, IEEE 802.1p, IEEE 802.3x, IEEE802.3af, IEEE802.3at
Network Medium	100/1000BASE-TX: 5 class and above non shielded twisted pair
Data Distance	≤100m
Switch Capability	12Gbps
Forwarding Mode	Store and forward
Forwarding Rate	100BASE-tx: 0.1488Mpps/port
	1000BASE-T: 1.488Mpps/port
MAC Address	MAC address table 2K
Port Function	Power priority mechanism, fast and forward, MAC automatic learning and aging
	IEEE802.3X Full-duplex and mode and backpressure for Half-duplex mode
LED Indicator	Each port occupied 1 LINK/ACT. 100Mbps
	PoE Status Indicator, Whole power indicator
Working Environment	Working temperature: -10°-- 55°C
Input	230VAC, 50/60Hz
Weight	850g
Size	200mm×118mm×44mm(L×W×H)