

## Desktop switch

PS16FE+2GE+1SFP



## Key Features

- 16\*10/100Mbps PoE port; 2\*100/1000Mbps Up Link; 1\*100/1000Mbps SFP
- 250m Distance; VLAN support
- Support IEEE802.3af/at
- Whole Power:250W (52V 4.8A)
- All port supported by MDI/MDIX auto flip and self-negotiation
- Supply 18 10/100/1000Mbps adaptive high speed forwarding data packet non-lost port.
- Support IEEE802.3x flow control for Full-duplex mode and backpressure for Half-duplex mode.
- Each port max. power supply reached 30W

### Specifications

Model	PS16FE+2GE+1SFP
Product	16+2+1 port 250m PoE switch (Built-in)
PoE Port	1 to 16 port support IEEE802.3af/at
Up link port	17th-19th port support 1000Mbps
PoE output	15.4W/30W IEEE802.3af/at
PoE whole power	≤250W
PoE type	End-span
Power distance	≤250m
Network Standard	IEEE 802.3, IEEE802.3u, 802.3x, 802.3af/at
Network Medium	100/1000BASE-TX: 5 class and above non shielded twisted pair
Data Distance	≤250m
Switch capability	12Gbps
Forwarding Mode	Store and forward
Forwarding Rate	10BASE-tx:14880pps/port
	100BASE-tx: 148800pps/port
	1000BASE-tx: 1488000pps/port
MAC Address	2K MAC address table
Port Function	Power priority mechanism, fast and forward, MAC automatic learning and aging
	IEEE802.3X Full-duplex and mode and backpressure for Half-duplex mode
LED Indicator	LINK/ACT. 100Mbps; POE Status indicator; POWER indicator; EXTENDER indicator
Working Environment	Working Temperature: -10°-- 55°C
Power	230VAC/255W (internal power supply)
Weight	2kg
Size	270*180*44mm(L*W*H)