




PTZ-6222ER-X30P-B

2MP 30x IR Network PoE+ PTZ Dome Camera

- 30X Optical Zoom, Accurate and fast focusing
- Smart IR, up to 150 m IR distance
- Optical glass window with higher light transmittance
- IR anti-reflection window to increase the infrared transmittance
- H.265, H.264, MJPEG triple stream + Smart Encoding
- Embedded smart algorithm
- ONVIF Conformance
- Innovative snow-removing function
- More effective heat dissipation system
- Intelligent temperature control technology
- 6 KV surge protection designed for network interface



Specifications

Sensor	1/3", 2 megapixel, progressive scan, CMOS
Shutter	Auto/Manual, 1/6~1/100000 s
Iris	Auto/Manual; F1.6 ~ F4.4
Lens	4.5 ~ 135 mm (30x optical zoom), 62.9° (wide) ~ 2.3° (tele)
Zoom/Focus	Motor drive
Min. Illumination	Colour: 0.03 lux (F1.6, AGC ON), 0 lux with IR
Day/Night	IR-cut filter with auto switch (ICR)
IR Range	Up to 150m IR range
S/N	>52dB
WDR	Digital WDR
Max. Resolution	1920 × 1080
Video Compression	H.265 + Smart Encode, H.264, MJPEG
Frame Rate	1080P (1920*1080): Max. 30 fps; 720P (1280*720): Max. 30 fps; D1 (720*576): Max. 25 fps
Digital Zoom / HLC	Supported / Supported
Video Streaming	Triple
OSD	Up to 8 OSDs
Privacy Mask	Supported
Behavior Detection	Intrusion, crossing line, motion detection (22x18 grid / 4 area)
Exception Detection	Audio detection
Intelligent Identification	Face detection
Statistical Analysis	People counting
Audio Compression	G.711a/G.711u
Two-way audio	Supported
Storage	Micro SD, up to 128 GB with ANR (Automatic Network Recovery) Function
Protocols	L2TP, IPv4, IPv6, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SIP, STUN, 802.1x, (Telnet default: OFF)
Compatible Integration	ONVIF, API
Audio I/O	Audio cable, Input: impedance 35 kΩ; 2 V [p-p], Output: impedance 600 Ω; 2 V [p-p]
Alarm I/O	1/ 1
Network	1 RJ45 10M/100M Base-TX Ethernet
Video Output	1 BNC, impedance 75 Ω; amplitude 1 V [p-p]
Pan Range / Pan Speed	360° (endless) / 0.1°/s ~ 240°/s, Preset speed: 300°/s
Tilt Range / Tilt Speed	-15° ~ +90° (auto reverse) / 0.1° ~ 160°/s, Preset speed: 240°/s
Prestes / Patrols / Patterns	Max. 256 presets / Max 16 patrols, up to 32 preset positions per patrol / Max 16 patterns with 15 minutes per pattern. Note: Total number of Patterns + Patrols = 16
Power	24 V AC ±25%, 24 V DC v, or PoE+ (IEEE802.3 at), Power consumption: 9 ~ 42W
Dimensions (Ø x H), Weight	Ø227 x 359.4 mm, 5.28 kg
Working Environment	-40°C ~ +65°C, Humidity ≤ 95% RH(non-condensing)
Ingress Protection	IP67