




PTZ-6252SL-X33UP

2MP 33x Starlight Laser IR Network PoE+ PTZ Camera

- Stalight
- 33X Optical Zoom, Accurate and fast focusing
- Smart IR, up to 30m IR distance
- Vari-focal laser: 30m to 500m, proportional to optical zoom of camera module
- Optical glass window with higher light transmittance
- IR anti-reflection window to increase the infrared transmittance
- H.265, H.264, MJPEG triple stream + Smart Encoding
- Embedded smart algorithm
- ONVIF Conformance
- Built in EIS (Electronic Image Stabilization)
- More effective heat dissipation system
- Intelligent temperature control technology
- 6 KV surge protection designed for network interface



Specifications

Sensor	1/2.8", 2 megapixel, progressive scan, CMOS
Shutter	Auto/Manual, 1/6~1/100000 s
Iris	Auto/manual, F1.6-5.3
Lens	4.5 ~ 148.5 mm (33x Optical Zoom), 62.67° (Wide) ~ 2.82° (Tele), 16x Digital zoom
Zoom/Focus	Motor drive
Min. Illumination	Colour: 0.002 lux (F1.6, AGC ON), 0 lux with IR
Day/Night	IR-cut filter with auto switch (ICR)
IR Range	Smart IR Up to 30m, Vari-focal Laser IR up to 500m
S/N	>52dB
WDR	True WDR (max. 120dB)
Max. Resolution	1920 × 1080 @60fps
Video Compression	H.265 + Smart Encode, H.264, MJPEG, H.264 code profile: Baseline Profile, Main Profile, High Profile
Frame Rate	Main stream: 1080P (1920x1080): Max. 60 fps; 1080P (1920x1080): Max. 60 fps; 3rd stream: D1 (720x576): Max. 60 fps
HLC / BLC / EIS	Supported / Supported / Supported
Video Streaming	Triple
OSD / Privacy Mask	Up to 8 OSDs / Up to 24 areas
Behavior Detection	Intrusion, Loitering, Crossing line, Motion detection (22x18 grid / 4 area)
Exception Detection	Audio detection
Intelligent Identification	Face detection, Defocus, Scene Change
Statistical Analysis	People counting
General functions	Watermark, IP Address Filtering, Tampering Alarm, Alarm input, Alarm output, Access Policy, ARP Protection, RTSP Authentication, User Authentication
Audio Compression	G.711 / Supported
Storage	Micro SD, up to 128 GB with ANR (Automatic Network Recovery) Function
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, (Telnet default: OFF)
Compatible Integration	ONVIF(Profile S, Profile G), API
Audio I/O	Audio cable, Input: impedance 35 kΩ; 2 V [p-p], Output: impedance 600 Ω; 2 V [p-p]
Alarm I/O	1/ 1
Network	1 RJ45 10M/100M Base-TX Ethernet
Pan Range / Pan Speed	360° (endless) / 0.1°/s ~ 240°/s, Preset speed: 300°/s
Tilt Range / Tilt Speed	-15° ~ +90° (auto reverse) / 0.1° ~ 160°/s, Preset speed: 240°/s
Prestes / Patrols / Patterns	Max. 1024 presets / Supported /Supported
Power	24 V AC ±25% or 24 V DC ±25% or PoE+ (IEEE802.3 at, PSE required), Power consumption: 8 ~ 47W
Dimensions (Ø x H), Weight	Ø227 x 359.4mm, 5.6kg
Working Environment	-40°C ~ +70°C, Humidity ≤ 95% RH(non-condensing)
Ingress Protection	IP66