



XVR-8104

6in1 H.264+ 5MPix AHD, TVI, CVI, XVI, CVBS + IP Video Recorder

- Support 4ch 5M/4M unreal-time encoding
- Support 4ch 1080p realtime video recording
- Support AHD, TVI, CVI, XVI, CVBS, IP video input
- HDMI/VGA simultaneous video output
- Mini 1U Case, 1 SATA(Up to 8TB)
- 1 x 10/100Mbps auto-sensing Ethernet port, RJ45 port
- Automatic networking support, a key to add equipment
- Support Onvif protocol
- Cloud services, P2P, alarm information push to phone
- Support remote access, support ARSP
- Support DHCP, FTP, DNS, DDNS, NTP, UPNP, E-MAIL, 3G, WIFI, IP search, Alarm center, etc
- Mobile phone remote monitoring (iOS, Android)
- Support for more than twenty languages
- Perfect protection circuit, unique triple watchdog function
- Support WEB, CMS, VMS, XMEYE Platform



Specifications

Video Input	4 x BNC (Support Coaxitron / XVI Control)
Audio Input	4-ch, RCA
HDMI Output	1920x1080, 1600x1200, 1280x1024, 1280x720, 1024x768
VGA Output	1920x1080, 1600x1200, 1280x1024, 1280x720, 1024x768
Audio Output	1-ch, RCA
Recording Resolution	4 x 5M@11fps(AHD) 4 x 4M@15fps(AHD) 4 x 3M@18fps(AHD) 4 x 1080P@25fps(4in1) 4 x 720P(4in1)
Multi mode	Hybird: 2 x 5M-max (analog) + 2 x 5M-max (network, NETIP/ONVIF)
NVR / IP-only mode	8 x 1080p + 8 x 960p; 4 x 5M; 4 x 3M
Synchronous Playback	4-ch (1ch in 16 x IP recording mode)
Compression	H.264, H.264+
Storage Interface	1 SATA interface - internal
Capacity	up to 8TB
Record Mode	Manual>Alarm>Motion detection>Timing
Inquire mode	Inquire by Time/Calendar/Event/Channel
Storage mode	HDD Storage, Network Storage
Backup	Network, USB
Network Interface	1 x 10/100Mbps Ethernet port, RJ45 port
PTZ Control	1 x RS485, Support for multiple PTZ protocol
USB Interface	2 x USB2.0 ports
CPU	Hi3521A
Alarm I/O	0 / 0
Power Supply	12V/2A
Consumption (without HDD)	≤ 15 W
Working Temperature	0°C ~ + 55°C
Working Humidity	10% -90% RH
Dimensions / Weight (W/O HDD)	255mm(L) x 236mm(W) x 44mm(H) / 1kg