



XVR-8216A

6in1 H.264+ 5MPix AHD, TVI, CVI, XVI, CVBS + IP Video Recorder

- Support 16ch 5M/4M unreal-time encoding
- Support 16ch 1080p@25fps realtime video recording
- Support AHD, TVI, CVI, XVI, CVBS, IP video input
- HDMI (max. 3840x2160)/VGA (max. 1920x1080) simultaneous video output
- 1U Case, 2 SATA(Up to 8TB/pcs)
- 1 x 10/100Mbps auto-sensing Ethernet port, RJ45 port
- Automatic networking support, a key to add equipment
- Support Onvif protocol
- Cloud services, P2P, alarm information push to phone
- Support remote access, support ARSP
- Support DHCP, FTP, DNS, DDNS, NTP, UPNP, E-MAIL, 3G, WIFI, IP search, Alarm center, etc
- Mobile phone remote monitoring (iOS, Android)
- Support for more than twenty languages
- Perfect protection circuit, unique triple watchdog function
- Support WEB, CMS, VMS, XMEYE Platform



Specifications

Video Input	16 x BNC (Support Coaxitron / XVI Control)
Audio Input	4-ch, RCA
HDMI Output	3840x2160, 1920x1080, 1600x1200, 1280x1024, 1280x720, 1024x768
VGA Output	1920x1080, 1600x1200, 1280x1024, 1280x720, 1024x768
Audio Output	1-ch, RCA
Recording Resolution	16 x 5M@11fps(AHD), 16 x 4M@15fps(AHD), 16 x 3M@18fps(AHD), 16 x 1080P@25fps (5in1)
Multi mode	Hybird: 8 x 5M-max (analog) + 8 x 5M-max (network, NETIP/ONVIF)
NVR / IP-only mode	8 x 5M; 16 x 3M; 32 x 1080p
Synchronous Playback	8 ch
Compression	H.264, H.264+
Storage Interface	2 pcs SATA interface - internal
Capacity	up to 8TB/pcs
Record Mode	Manual, Alarm, Motion detection, Timing
Inquire mode	Inquire by Time/Calendar/Event/Channel
Storage mode	HDD Storage, Network Storage
Backup	Network, USB
Network Interface	1 x 10/100Mbps Ethernet port, RJ45 port
PTZ Control	1 x RS485, Support for multiple PTZ protocol
USB Interface	2 x USB2.0 ports
CPU	2 xHi3531A
Alarm I/O	16 / 4
Power Supply	12VDC/4A
Consumption (without HDD)	≤ 15 W
Working Temperature	0°C ~ + 55°C
Working Humidity	10% -90% RH
Dimensions / Weight (W/O HDD)	350mm(L) x 296mm(W) x 44mm(H) / 2kg